


# DATA CLEANING



**JYOTHISHMATHI INSTITUTE OF TECHNOLOGY AND SCIENCE**

Prepared By  
M.MAMATHA  
ASST. PROFESSOR  
CSE

# Chapter 3: Data Preprocessing

- Data Preprocessing: An Overview 
  - Data Quality
  - Major Tasks in Data Preprocessing
- Data Cleaning
- Data Integration
- Data Reduction
- Data Transformation and Data Discretization
- Summary

# Data Quality: Why Preprocess the Data?

- Measures for data quality: A multidimensional view
  - Accuracy: correct or wrong, accurate or not
  - Completeness: not recorded, unavailable, ...
  - Consistency: some modified but some not, dangling, ...
  - Timeliness: timely update?
  - Believability: how trustable the data are correct?
  - Interpretability: how easily the data can be understood?

# Data Cleaning

- Data in the Real World Is Dirty: Lots of potentially incorrect data, e.g., instrument faulty, human or computer error, transmission error
  - incomplete: lacking attribute values, lacking certain attributes of interest, or containing only aggregate data
    - e.g., *Occupation*=" " (missing data)
  - noisy: containing noise, errors, or outliers
    - e.g., *Salary*="−10" (an error)
  - inconsistent: containing discrepancies in codes or names, e.g.,
    - *Age*="42", *Birthday*="03/07/2010"
    - Was rating "1, 2, 3", now rating "A, B, C"
    - discrepancy between duplicate records
  - Intentional (e.g., *disguised missing* data)
    - Jan. 1 as everyone's birthday?

# Incomplete (Missing) Data

- Data is not always available
  - E.g., many tuples have no recorded value for several attributes, such as customer income in sales data
- Missing data may be due to
  - equipment malfunction
  - inconsistent with other recorded data and thus deleted
  - data not entered due to misunderstanding
  - certain data may not be considered important at the time of entry
  - not register history or changes of the data
- Missing data may need to be inferred

# How to Handle Missing Data?

- Ignore the tuple: usually done when class label is missing (when doing classification)—not effective when the % of missing values per attribute varies considerably
- Fill in the missing value manually: tedious + infeasible?
- Fill in it automatically with
  - a global constant : e.g., “unknown”, a new class?!
  - the attribute mean
  - the attribute mean for all samples belonging to the same class: smarter
  - the most probable value: inference-based such as Bayesian formula or decision tree

# Noisy Data

- **Noise**: random error or variance in a measured variable
- **Incorrect attribute values** may be due to
  - faulty data collection instruments
  - data entry problems
  - data transmission problems
  - technology limitation
  - inconsistency in naming convention
- **Other data problems** which require data cleaning
  - duplicate records
  - incomplete data
  - inconsistent data

# How to Handle Noisy Data?

- Binning
  - first sort data and partition into (equal-frequency) bins
  - then one can smooth by bin means, smooth by bin median, smooth by bin boundaries, etc.
- Regression
  - smooth by fitting the data into regression functions
- Clustering
  - detect and remove outliers
- Combined computer and human inspection
  - detect suspicious values and check by human (e.g., deal with possible outliers)



# Data Cleaning as a Process

- Data discrepancy detection
  - Use metadata (e.g., domain, range, dependency, distribution)
  - Check field overloading
  - Check uniqueness rule, consecutive rule and null rule
  - Use commercial tools
    - Data scrubbing: use simple domain knowledge (e.g., postal code, spell-check) to detect errors and make corrections
    - Data auditing: by analyzing data to discover rules and relationship to detect violators (e.g., correlation and clustering to find outliers)
- Data migration and integration
  - Data migration tools: allow transformations to be specified
  - ETL (Extraction/Transformation/Loading) tools: allow users to specify transformations through a graphical user interface
- Integration of the two processes
  - Iterative and interactive (e.g., Potter's Wheels)